


W-406-TU

**URETHANE
TREAD SYMBOL "U"
DUROMETER - SHORE 95 "A"**

A Urethane Tread moulded and bonded to a steel core.
Recommended for heavy loads and rough floor conditions.
Resistant to a wide range of chemicals, oils and solvents.
Withstands temperature ranges from 25°F below 0 up to 200°F.
Resists abrasion and flat spotting.



W-8510-YU

**LOW EFFORT URETHANE
TREAD SYMBOL "LE"
DUROMETER - SHORE 80 "A"**

Glass reinforced nylon core
Outperforms conventional urethane wheels
Long lasting, resistant to chemicals
Available in other hardness ratings
Highly resilient
Rolls smoothly on any floor material
Suitable for wet applications



W-405-PLE

URETHANE - U

WHEEL DIAMETER	TREAD WIDTH	LOAD CAP./LBS	ROLLER BEARING	TAPERED BEARING	BORE SIZE	HUB LENGTH	USED IN CASTER SERIES
3-1/2"	2"	800	W-403.5-TU		1/2"	2-5/16"	400
4"	1-3/8"	600	W-74-TU		3/8"	1-3/4"	70
4"	2"	900	W-404-TU		1/2"	2-5/16"	400
5"	1-3/8"	600	W-75-TU		3/8"	1-3/4"	70
5"	2"	1000	W-405-TU		1/2"	2-5/16"	400
6"	1-3/8"	600	W-76-TU		3/8"	1-3/4"	70
6"	2"	1000	W-406-TU		1/2"	2-5/16"	400
6"	2-1/4"	1500	W-806-TU		3/4"	2-3/4"	700/800
6"	3"	2500	W-5006-TU	W-5006-YU	3/4", 1"	3-3/8"	900, 5000, 5200
8"	2"	1000	W-408-TU		1/2"	2-5/16"	400
8"	2-1/2"	1800	W-808-TU		3/4"	2-3/4"	700/800
8"	3"	3000	W-5008-TU	W-5008-YU	3/4", 1"	3-3/8"	900, 5000, 5200
10"	3"	3500	W-5010-TU	W-5010-YU	3/4", 1"	3-3/8"	900, 5000, 5200
10"	4"	8000		W-8010-YU	1-1/2"	4-1/2"	WHEEL ONLY
10"	5"	10,000		W-8510-YU	1"	5-1/2"	SL-8510
12"	3"	4000	W-5012-TU	W-5012-YU	3/4", 1"	3-1/4"	900,5000,5200
16"	5"	8400		W-8016-YU	1-1/2"	5-1/2"	8216

Additional Bore Sizes available.

400 Series - 3/4"

700 Series - 1/2", 1"

5000 Series - 1-1/4"

CASTERS & EQUIPMENT CO.

LOW EFFORT URETHANE - LE

WHEEL DIAMETER	TREAD WIDTH	LOAD CAPACITY	BALL BEARING	PRECISION SEALED BALL BEARING	BORE SIZE	HUB LENGTH	USED IN CASTER SERIES
4"	2"	630		W-404-PLE	1/2"	2-5/16"	400
6"	2"	700		W-406-PLE	1/2"	2-5/16"	400
8"	2"	700		W-408-PLE	1/2"	2-5/16"	400
8"	3"	2100		W-5008-PLE	3/4", 1"	3 3/8"	900, 5000, 5200